

AD-A126 686

REAL-TIME MONITORING OF THE VISUAL EVOKED POTENTIAL(U)  
NAVAL AIR DEVELOPMENT CENTER WARMINSTER PA AIRCRAFT AND  
CREW SYSTEMS TECHNOLOGY DIRECTORATE J G NELSON ET AL.  
JUL 82 NADC-82205-60

1/1

UNCLASSIFIED

F/G 5/10

NL




END

DATE

FILMED

5-83

DTIC



MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

12



# REAL-TIME MONITORING OF THE VISUAL EVOKED POTENTIAL

J. G. Nelson and L. Hrebien  
Aircraft and Crew Systems Technology Directorate  
NAVAL AIR DEVELOPMENT CENTER  
Warminster, Pennsylvania 18974

JULY 1982

INTERIM REPORT

*Approved for Public Release; Distribution Unlimited*

ADA 126686

DTIC FILE COPY

Prepared for  
NAVAL AIR SYSTEMS COMMAND  
Department of the Navy  
Washington, D. C. 20361

DTIC  
ELECTE  
APR 11 1983  
S D E

83 04 11 017


## NOTICES

**REPORT NUMBERING SYSTEM** – The numbering of technical project reports issued by the Naval Air Development Center is arranged for specific identification purposes. Each number consists of the Center acronym, the calendar year in which the number was assigned, the sequence number of the report within the specific calendar year, and the official 2-digit correspondence code of the Command Office or the Functional Directorate responsible for the report. For example: Report No. NADC-78015-20 indicates the fifteenth Center report for the year 1978, and prepared by the Systems Directorate. The numerical codes are as follows:

CODE	OFFICE OR DIRECTORATE
00	Commander, Naval Air Development Center
01	Technical Director, Naval Air Development Center
02	Comptroller
10	Directorate Command Projects
20	Systems Directorate
30	Sensors & Avionics Technology Directorate
40	Communication & Navigation Technology Directorate
50	Software Computer Directorate
60	Aircraft & Crew Systems Technology Directorate
70	Planning Assessment Resources
80	Engineering Support Group

**PRODUCT ENDORSEMENT** – The discussion or instructions concerning commercial products herein do not constitute an endorsement by the Government nor do they convey or imply the license or right to use such products.

APPROVED BY:



DATE:

16 MAR 1983

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NADC-82205-80	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Real-Time Monitoring of the Visual Evoked Potential		5. TYPE OF REPORT & PERIOD COVERED Interim
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) John G. Nelson, Leonid Hrebien, Ph.D		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Aircraft and Crew System Technology Directorate Naval Air Development Center Warminster, Pa. 18974		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 61153N, WRO41-01, WRO4101001, DG108
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Air Systems Command Research Administrator (AIR-310) Washington, D.C. 20360		12. REPORT DATE July 1982
		13. NUMBER OF PAGES 5
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  Approved for Public Release; Distribution Unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES Presented at Aerospace Medical Assoc. Annual Meeting, Bal Harbour, Florida, May 10-13, 1982		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)  Evoked Responses, Acceleration Physiology, Human Subjects, Evoked Potential, Vision, Steady-State Evoked Potentials.		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  Subjects can experience loss of consciousness (LOC) during exposure to sufficiently high +G <sub>x</sub> acceleration. LOC is usually preceded by decreased visual sensitivity, dimming of the visual field, peripheral light loss (PLL) and central light loss. Real-time monitoring of PLL as a measure of +G <sub>x</sub> tolerance on the human centrifuge presently requires an active response by the subject.  In contrast, the visual evoked potential (VEP) also reflects the integrity of the visual system and requires only the passive response of viewing a visual stimulus.		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE  
S/N 0102- LP-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

> A preliminary evaluation of the Steady-state VEP for real-time monitoring of visual functioning was accomplished with a computer controlled dual-channel, Fast Fourier Transform (FFT) signal analyzer. Since significant degradation of visual functioning must be recognized in less than approximately four seconds, we required a previously unattained efficiency in producing and measuring the VEP. Using the Coherence Function and the expectation for the variance of a weighted sum of variables we developed analytic methods and instrumentation for reducing the results of the FFT processing to unidimensional measures having a known and maximal signal-to-noise ratio, with measures available at 1 1/2 sec. intervals.

Preliminary tests on six subjects indicate that the technique may have adequate stability as a measure of G-tolerance. Stimulus Interruption produces a rapid loss of response, with recovery somewhat slower. However, the measure is considerably more stable for some subjects than for others. Further testing is in progress.

S/N 0102- LR-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

TABLE OF CONTENTS

LIST OF FIGURES .....	ii
LIST OF TABLES .....	ii
INTRODUCTION .....	1
METHOD .....	1
RESULTS AND CONCLUSIONS .....	1
REFERENCES .....	5

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	



LIST OF FIGURES

Figure		Page
1	Mean Percent Vision For All Real-Time Runs .....	3
2	Specimen Real-Time Run For Subject with Low Predicted and Obtained Standard Deviation (See Table I) .....	4

LIST OF TABLES

Table		Page
I	The Expected Standard Deviations, Obtained Standard Deviations, and Mean Percent Vision for Real-Time Runs (Frames 4-34) .....	2



## INTRODUCTION

Subjects can experience loss of consciousness (LOC) during exposure to sufficiently high +Gz acceleration. LOC is usually preceded by decreased visual sensitivity, dimming of the visual field, peripheral light loss (PLL) and central light loss. Real-time monitoring of PLL as a measure of +Gz tolerance on the human centrifuge presently requires an active response by the subject.

In contrast, the visual evoked potential (VEP) also reflects the integrity of the visual system and requires only the passive response of viewing a visual stimulus. (4)

A preliminary evaluation of the Steady-state VEP for real-time monitoring of visual functioning was accomplished with a computer controlled dual-channel Fast Fourier Transform (FFT) signal analyzer. Since significant degradation of visual functioning must be recognized in less than approximately four seconds, we required a previously unattained efficiency in producing and measuring the VEP. Using the Coherence Function (1) and the expectation for the variance of a weighted sum of variables (2) we developed analytic methods and instrumentation for reducing the results of the FFT processing to a unidimensional measure (which we label "Percent Vision"), having a known and maximal signal-to-noise ratio, with measures available at 1½ second intervals. (3)

## METHOD

This approach was tested on six male Naval Enlisted and Officer volunteers under static (non-centrifuge) conditions. The subjects sat in front of a diffuse strobe light flickering simultaneously at 12.8 and 16.0 Hz. This was timed and controlled from the internal clock signal of an HP3582A low frequency spectrum analyzer which was set to retrigger every 1.5625 seconds and generated an FFT for each of these time frames in the frequency range of 0-100 Hz, with a spectral resolution of 0.8 Hz. Standard scalp electrodes (Oz, Cz, mastoid ref.) were used to monitor the EEG. Each subject sat through four runs lasting about one minute each on two different days. The first of each four runs was a parameter estimation run and the next three, taken less than two minutes apart, were used for determination of "Percent Vision". For these three runs the strobe light was occluded for about five seconds and then exposed again near the end of each run to simulate an episode of loss of vision.

During the parameter estimation runs, we collected 32 FFT's and estimated the copower, cross-power, phase angle, and coherence of the ensemble. These parameters were used to calculate a complex weighting function to be applied to single FFT's in real-time to produce the single variable, "% Vision". The weighting function performs magnitude normalization, rotation of axis such that the VEP component becomes positive real, and produces scalars which when summed result in a variable which has maximal signal-to-noise ratio. (This method assumes stationarity, normal distribution, uncorrelated "noise", correlated "signal").

## RESULTS AND CONCLUSIONS

In all runs, a five second delay of the data collection, after turning on the strobe, was used to permit the response to reach a steady-state. In Figure 1, the first 2-3 plotted points indicate that a total delay of 8-10 seconds should be used in further applications. In the real-time runs, the strobe was occluded for three frame times beginning approximately at frame 34. In Figure 1, the values for Frames 35-38 indicate that a three frame loss of stimulus has a major effect on only four frames. Frames 36-37, clustering as they do at zero, indicate that coherent electronic noise was not corrupting the measurement.

Taking Frames 4-34 as quasi-stationary, Table 1 presents the summary results for each of the 36 real-time runs. The expected standard deviation, based upon the parameter estimation runs, ranges from 17.0 to 30.4, while the obtained values ranged from 15.4 to 36.8. The correlation between E[SD] and real-time SD was +.62.

Mean Percent Vision, ranging from 59.6 to 106.5, was not related to either expected or obtained SD ( $r = +.12$  and  $+.07$  respectively). This reduced signal amplitude would seem to require a non-stationarity of the VEP's phase angles and/or relative magnitudes (magnitude as a function of frequency). Further data and analysis are required to estimate the source of this effect, and appropriate methods for dealing with it.

Figure 2, in addition to showing that the monitoring method is useable with the "better" subjects, also shows the effectiveness and cost of using a "Two-Point Smooth": the displayed result at frame 24 is moved up substantially, but the zero vision point at frame 35 is delayed by one frame-time. Since we can not simply reject time-frames contaminated by eye-blink or other artifacts such smoothing provides a simple and reasonably effective method.

Overall, the results of this experiment indicate that while improvements in the method are required, if we are to have an effective real-time monitor for visual functioning, such improvements are not only possible, but feasible. Procedure modification, changes in stimulus parameters and provision of auditory or tactile feedback to the subject, all promise some improvement. Measurement of the separate responses at O1 and O2, instead of just O2, should give a considerable improvement in detection.

TABLE 1. THE EXPECTED STANDARD DEVIATIONS, OBTAINED STANDARD DEVIATIONS, AND MEAN PERCENT VISION FOR REAL-TIME RUNS (Frames 4-34).

SESSION-SUBJECT	EXPECTED SD	RT-1 SD	RT-2 SD	RT-3 SD	RT-1 MEAN	RT-2 MEAN	RT-3 MEAN
1-1	24.9	29.6	27.6	27.2	82.1	106.3	90.5
1-2	18.2	24.5	22.9	16.7	99.7	80.6	67.9
1-3	18.5	15.4	21.8	19.1	85.9	77.9	74.7
1-4	21.6	31.0	28.4	21.1	79.1	64.8	59.6
1-5	17.0	18.3	19.1	20.4	94.1	83.7	77.1
1-6	22.0	25.8	19.2	20.1	86.3	73.4	79.7
2-1	30.4	24.9	26.3	33.9	64.8	79.2	97.9
2-2	18.0	19.5	26.7	22.5	91.7	81.7	69.5
2-3	24.0	22.8	28.8	20.0	106.5	95.2	105.2
2-4	29.5	24.7	30.1	32.8	97.6	86.2	90.5
2-5	17.5*	21.0	18.6	17.5*	101.2	91.3	93.3*
2-6	21.8	23.8	22.5	36.8	80.9	89.0	79.7

\*Shown as Figure 2, Specimen Real-Time Run.




Figure 1 - Mean Percent Vision For All Real-Time Runs




Figure 2 - Specimen Real-Time Run For Subject with Low Predicted and Obtained Standard Deviation (See Table I)

REFERENCES

1. Bendat, J. S., and A. G. Piersol. Random Data: Analysis and Measurement Procedures. New York: Wiley - Interscience, 1971.
2. Guilford, J. P., and B. Fruchter. Fundamental Statistics in Psychology and Education (6th ed.). New York: McGraw - Hill, 1977.
3. Nelson, J. G., J. J. Palumbo, and M. M. Cohen. Use of the coherence function in analysis of steady-state visual evoked potential (VEP), in Research Program Review, Aircrew Physiology, Naval Air Systems Command Research and Technology Group, Oct, 1980.
4. Regan, D. Steady-state evoked potentials. J. Opt. Soc. Am., 67:1475, 1977.

REPORT NO. NADC-82005-60

D I S T R I B U T I O N   L I S T   ( c o n t i n u e d )

	<u>No. of Copies</u>
Dr. Jerry I. Nelson, Assistant Professor of Experimental Ophthalmology, N.Y. University.....	1
Royal Air Force Institute of Aviation Medicine, Farnborough, U.K. ....	1
Defense & Civil Institute of Environmental Medicine, Downsview, Canada.....	1
German Air Force Institute of Aerospace Medicine, Fürstenfeldbruck, West Germany.....	1
Institute of Aviation Medicine, Oslo, Norway.....	1

ME  
-8